

CANIS PRO 415 PH

NORDIC LIGHTS® Canis PRO 415 Phenom Optics an extremely useful work light delivering a three-in-one optical solution through our Phenom Optics solution (patent pending). With this work light mounted on your heavy-duty vehicle, you will have accent lighting with soft illumination directed upwards as a guide light for lifting or other operations and efficient task lighting to illuminate the work area both directly in front of and further from the vehicle. Most importantly, people and other vehicles working nearby will not be blinded thanks to the glarefree zone it creates.

This LED work light is compact and lightweight, ideal for vehicles in material handling and construction. The Canis PRO 415 PH offers effective illumination with an operational lumen output of 1500 lm and excellent colour rendering in warm, natural hues. It has an asymmetrical wide flood light pattern and withstands vibrations of up to 8 Grms. Thanks to its glass lens and new strengthened aluminium housing, this work light has a high level of mechanical, thermal and corrosion resistance.



Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.

TECHNICAL DATA

Theoretical Lumens Output	1950 lm
Operational Lumens Output	1500 lm
Colour Temperature	5000 K
Nominal Voltage DC	12 V 24 V
Input Voltage DC	9 - 16 V 18 - 32 V
Power Consumption	28 W
Nominal Current at	12V=2.4A, 24V=1.2A

Vibration	8Grms 24-2000Hz	
Lens	Glass	
Body / Housing	Aluminum	
Weight	0.6 kg	
IP Rating	IP68, IP6K9K	
Salt Spray Test	ISO 9227 240H	
EMC	CISPR 25 Class 5, EN 14982-2, ISO 13766, EN 12895, ISO 11452-2, EN 13309, ISO 7637-2	



-40°C +85°C (Overheat protected)	Operating Temperatures Electronics	Built-in Deutsch DT-2 (2-pin)	Connector
		Single Bolt M8	Mount
		60G	Shock
Wide Flood: 989-201B	Part Numbers		GHOOK



CONNECTORS




Built-in Deutsch DT-2 (2-pin)

KEY FEATURES

- Glare-free, will not blind people near the vehicle (PATENT PENDING WO2019073105)
- Maximum safety and high visibility with light focused on the desired areas
- Superior electromagnetic compatibility (CISPR 25 Class 5)

LIGHT PATTERNS

Canis PRO 415 PH, 1500lm Wide Flood



DRAWINGS



