

SCORPIUS PRO 415 PH

NORDIC LIGHTS® Scorpius PRO 415 Phenom Optics is an extremely useful work light delivering a three-in-one optical solution through our Phenom Optics solution (patent pending). With this work light mounted on your heavy-duty vehicle, you will have accent lighting with soft illumination directed upwards as a guide light for lifting or other operations and efficient task lighting to illuminate the work area both directly in front of and further from the vehicle. Most importantly, people and other vehicles working nearby will not be blinded thanks to the glarefree zone it creates.

This LED work light is compact and lightweight, ideal for vehicles in material handling and construction. The Scorpius PRO 415 PH offers effective illumination with an operational lumen output of 1500 Im and excellent colour rendering in warm, natural hues. It has an asymmetrical wide flood light pattern and withstands vibrations of up to 8 Grms. Thanks to its glass lens and new strengthened aluminium housing, this work light has a high level of mechanical, thermal and corrosion resistance.



Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.

TECHNICAL DATA

Theoretical Lumens Output	1950 lm	Vibration	8Grms 24-2000Hz
Operational Lumens Output	1500 lm	Lens	Glass
Colour Temperature	5000 K	Body / Housing	Aluminum
Nominal Voltage DC	12 V 24 V	Weight	0.6 kg
Input Voltage DC	24 V 9 - 16 V	IP Rating	IP68, IP6K9K
	18 - 32 V	Salt Spray Test	ISO 9227 240H
Power Consumption	28 W	EMC	CISPR 25 Class 5, EN
Nominal Current at	12V=2.4A, 24V=1.2A		14982-2, ISO 13766, EN 12895, ISO 11452-2, EN 13309, ISO 7637-2



Connector	Built-in Deutsch DT-2 (2-pin)	
Mount	Single Bolt M8	
WOULL		
Shock	60G	
SHOCK		

n)	Operating Temperatures	-40°C +85°C (Overheat protected)
10		p ,
18	Electronics	Isolated
G	Liootionioo	loolated
	Part Numbers	Wide Flood: 989-101B



CONNECTORS



Built-in Deutsch DT-2 (2-pin)

LIGHT PATTERNS



1 lx

10 ×

5

DRAWINGS

5

0

† 0 m→

KEY FEATURES

- Glare-free, will not blind people near the vehicle (PATENT PENDING WO2019073105)
- Maximum safety and high visibility with light focused on the desired areas
- Superior electromagnetic compatibility (CISPR 25 Class 5)



